



Holy Enterprise Limited

FL.2, No.12 North Ave.1, Industrial Rd. East, Gusan, Guzhen, Zhongshan, Guangdong, China

Specification

6-FM-8 12V8AH/20HR


Cells Per Unit	6
Voltage Per Unit	12
Capacity	8AH@20hr-rate to 1.8V per cell @ 25°C
Weight	Approx.2.35 kg (Tolerance±3%)
Max. Discharge Current	80 A(5sec)
Internal Resistance	Approx 33 mΩ
Operating Temperature Range	Discharge: -20°C~50°C Charge: 0°C~40°C Storage: -20°C~50°C
Normal Operating Temperature	25±3°C
Float Charging Voltage	2.25 to 2.27 VDC/unit Average at 25°C
Maximum Charging Current	2.25A
Equalization and Cycle service	2.35 to 2.40 VDC /unit Average at 25°C
Terminal	Terminal: F1/F2



Application

Alarm Systems
Electronic Toys
Medical Equipment
Cable Television
Communications Equipment
Electronic Cash Registers
Electric Test Equipment
Emergency lighting Systems
UPS

Dimension: 151(L) ×65(W) ×93(H) (Total 97 mm)



Constant Current Discharge Characteristics: A(25°C)


F.V/Time	5MIN	10MIN	15MIN	30MIN	60MIN	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.80V/cell	23.77	17.24	14.00	8.58	5.17	3.05	2.08	1.681	1.378	0.900	0.763	0.388
1.75V/cell	26.53	18.48	14.84	8.87	5.27	3.07	2.10	1.689	1.393	0.904	0.776	0.412
1.70V/cell	29.51	19.76	15.73	9.12	5.37	3.11	2.12	1.705	1.410	0.912	0.779	0.425
1.65V/cell	31.35	20.79	16.18	9.26	5.42	3.15	2.14	1.722	1.426	0.920	0.792	0.432
1.60V/cell	32.53	21.33	16.72	9.38	5.58	3.21	2.18	1.746	1.450	0.924	0.800	0.449

Constant Power Discharge Characteristics: W/Unit(25°C)


F.V/Time	5MIN	10MIN	15MIN	30MIN	60MIN	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.80V/cell	261.10	191.30	155.90	100.80	61.45	36.31	24.96	20.19	16.540	10.800	9.161	4.660
1.75V/cell	289.40	204.50	165.00	103.20	62.47	36.61	25.26	20.26	16.710	10.840	9.302	4.948
1.70V/cell	317.00	213.30	174.10	105.40	63.33	36.91	25.36	20.45	16.910	10.940	9.400	5.092
1.65V/cell	333.30	222.10	176.40	106.30	63.80	37.15	25.46	20.62	17.080	11.020	9.490	5.188
1.60V/cell	342.20	226.80	179.00	107.40	64.75	37.47	25.51	20.67	17.170	11.060	9.580	5.379

All mentioned values are average values.


Discharge Characteristics Curve




Charging Characteristics Curve




Cycle life in relation to depth of Discharge




Temperature effects on Capacity




Relationship between charging voltage and temperature



Self-discharge Characteristics



Temperature effects on Float life



Life Characteristics of Standby use



Maintenance & Cautions

- ※ Every month, recommend inspection every battery voltage;
- ※ Every three months, recommend equalization charge once;
Equalization charge method:
Discharge: 100% rate capacity discharge;
Charge: Max. Current 0.3CA, constant voltage 2.35-2.4V/Cell;
- ※ Effect of temperature on float charge voltage: -3mV/Cell;

CONTACT Us

Add: FL.2, No.12 North Ave.1, Industrial Rd. East, Gusan, Guzhen, Zhongshan, Guangdong, China,
T: +86-760- 8862 5562 | **F:** +86-760-8862 5562
Email: sales@holybattery.com johny5@126.com
Website: www.holybattery.com