



Holy Enterprise Limited

FL.2, No.12 North Ave.1, Industrial Rd. East, Gusan, Guzhen, Zhongshan, Guangdong, China

Specification

6-FM-9

12V9AH/20HR




Cells Per Unit	6
Voltage Per Unit	12
Capacity	9AH@20hr-rate to 1.8V per cell @ 25°C
Weight	Approx.2.55 kg (Tolerance±3%)
Max. Discharge Current	90 A(5sec)
Internal Resistance	Approx 32 mΩ
Operating Temperature	Discharge: -20°C~50°C Charge: 0°C~40°C Storage: -20°C~50°C
Normal Operating Temperature	25±3°C
Float Charging Voltage	2.25 to 2.27 VDC/unit Average at 25°C
Maximum Charging Current	2.7A
Equalization and Cycle service	2.35 to 2.40 VDC /unit Average at 25°C
Terminal	Terminal: F1/F2



Application

Alarm Systems
Electronic Toys
Medical Equipment
Cable Television
Communications Equipment
Electronic Cash Registers
Electric Test Equipment
Emergency lighting Systems
UPS

Dimension: 151(L) ×65(W) ×112(H) (Total 116 mm)



Constant Current Discharge Characteristics: A(25°C)


F.V/Time	5MIN	10MIN	15MIN	30MIN	60MIN	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.80V/cell	23.21	17.74	13.56	8.48	4.76	2.94	2.25	1.835	1.530	1.031	0.841	0.446
1.75V/cell	26.44	19.60	14.68	8.88	4.95	3.05	2.32	1.890	1.570	1.049	0.852	0.450
1.70V/cell	29.51	21.41	15.78	9.29	5.14	3.16	2.39	1.939	1.611	1.064	0.863	0.456
1.65V/cell	32.71	23.26	16.85	9.72	5.31	3.27	2.46	1.994	1.654	1.080	0.877	0.461
1.60V/cell	35.17	24.62	17.62	10.12	5.50	3.38	2.54	2.049	1.698	1.093	0.887	0.469

Constant Power Discharge Characteristics: W/Unit(25°C)


F.V/Time	5MIN	10MIN	15MIN	30MIN	60MIN	2HR	3HR	4HR	5HR	8HR	10HR	20HR
1.80V/cell	249.42	194.58	150.72	96.30	54.97	34.12	26.21	21.46	17.95	12.19	9.97	5.29
1.75V/cell	278.10	211.26	160.92	99.72	56.82	35.21	26.95	22.01	18.35	12.37	10.09	5.34
1.70V/cell	303.66	226.68	170.46	103.32	58.62	36.32	27.66	22.51	18.76	12.52	10.21	5.39
1.65V/cell	329.10	241.80	179.34	106.98	60.24	37.35	28.31	23.05	19.20	12.68	10.36	5.45
1.60V/cell	349.80	251.04	184.80	110.28	61.98	38.39	29.09	23.60	19.64	12.80	10.46	5.54

All mentioned values are average values.


Discharge Characteristics Curve




Charging Characteristics Curve




Cycle life in relation to depth of Discharge




Temperature effects on Capacity




Relationship between charging voltage and temperature



Self-discharge Characteristics



Temperature effects on Float life



Life Characteristics of Standby use



Maintenance & Cautions

- ※ Every month, recommend inspection every battery voltage;
- ※ Every three months, recommend equalization charge once;
Equalization charge method:
Discharge: 100% rate capacity discharge;
Charge: Max. Current 0.3CA, constant voltage 2.35-2.4V/Cell;
- ※ Effect of temperature on float charge voltage: -3mV/Cell;

CONTACT Us

Add: FL.2, No.12 North Ave.1, Industrial Rd. East, Gusan, Guzhen, Zhongshan, Guangdong, China,
T: +86-760- 8862 5562 | **F:** +86-760-8862 5562
Email: sales@holybattery.com johny5@126.com
Website: www.holybattery.com